

5134 Digi-Fend Canvas Coating

PRODUCT INFORMATION

Matte, gloss and satin water based coating for canvas.

APPLICATION FIELD

WB 5132-WB5134 Digi-Fend coating have been specifically formulated to conserve, protect and enhance your fine art and canvas prints produced on digital inkjet printers. It will protect against moisture and it will also increase resistance to image fading.

APPLICATION PROCESS

Substrater	Canvas
Drying	Digi-Fend coating air dry in 20 to 30 minutes at normal room temperature.
Storage	Store at room temperature, below 100° F (38° C). Always avoid open flames and excessive heat exposure. Protect from freezing.
Packaging	Available in quarts, gallons and five-gallon pails. 30 and 50 gallon drums can be ordered.
SDS	Available upon request

GENERAL FEATURES

- Ready to coat
- Gloss, Matte & Satin finishes
- Non yellowing
- Protects against moisture
- Provides UV protection
- Helps to enhance colors
- Spray or Roll application

IMPORTANT NOTE

The information given in this technical sheet is not intended to be exhaustive and any person, using the product for any purpose other than that specifically recommended in this sheet without first obtaining written confirmation from us to the suitability of the product for the intended purpose, does so at his own risk.

While we endeavour to ensure that all advice we give about the product is correct we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product.

Therefore, unless we specifically agree in writing to do so, we do not accept any liability whatsoever or howsoever arising for the performance of the product or for any loss or damage arising out of the use of the product.

The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.


Willox

Phone: 1 800 561 8844