

3D and Embroidery Digital Transfer Printing

XINFLYING

XF-600S+XF-P4030

Cutting Plotter & UV DTF Integrated Printing Solution



3D Icon Printing Preferred



Printing Process



3D Embroidery & UV DTF Integrated Printer

Model	XF-600S
Print Head	4pcs Epson i3200-U1
Print Speed	Fastest Print Speed: 6PASS: 6m²/h Standard Print Speed: 6PASS: 3m²/h
DPI	720*1200
Print Width	24" (60CM)
Ink Type	UV ink
Color	CMYK+W+W+V
Humidity	35% to 80% RH
Media Type	Leather, Advertising, Fabric, Flexible Materials, etc.
Media Transmission	Media feeding system
RIP Software	Standard with RIIN or Printfactory; For Option: Maintop, PhotoPrint
Power Supply/Voltage	220V/110V; 11.3A/22.7A; 50HZ/60HZ
Power	2.5KW
Machine Size /Package Size	L2000*W820*H1600mm / L2150*W1020*H1640mm
Net Weight/Gross Weigh	275kg/330kg

Cutting Plotter

Model	XF-P4030
Cutting Area	420*300mm
Cutting Speed	1mm/s~800mm/s
Cutting Thickness/Accuracy	1.2mm maximum / 1.2mm以内; Cutting Accuracy: ±0.15mm
Cutting Pressure	1000g
Material Fixing Method	Vacuum Adsorption
Interface	USB; USB Drive Offline Operation; Ethernet Port
Rated Voltage/Power	220V AC ±10%, 50Hz; Air Pump Voltage : 220V; 0.37kW
Command Set	HPGL Compatible Format
Positioning Method	Camera Positioning System
Overall Dimensions	L77.5*W59*H21.5cm (Platform Height :8.5cm)
Package Size	Cutting Plotter : L95*W74*H40cm; Air Pump : L34*W34*H34cm
Gross Weight	Cutting Plotter : 34.4KG; Air Pump : 12.4KG

